



- 01 **Versatile:** 34 nozzles and 6 body choices
- 02 **Durable:** Tough factory-installed rubber cover
- 03 **Adjustable:** 50°–360° arc setting with easy through-the-top adjustment

## I-20 ROTORS

### *Diverse and Efficient to Meet Any Need*

Whether you've got a small area, sandy soil, or a mix of shrubs and grass, the I-20 is ready to water with efficiency and reliability. With 34 nozzle choices, a 4.9 to 14 m radius, and six body choices, the I-20 is an indispensable rotor. Recent improvements include automatic arc return; non-reversing, adjustable arc from 50° to 360°, and a non-strippable, vandal-proof drive mechanism. Optional pressure-regulated bodies will take incoming pressures of 3.4 to 6.9 bar; 345 to 690 kPa and reduce them to 3.1 bar; 310 kPa, saving up to 25 percent more water. Additional features like FloStop® control, easy through-the-top arc adjustment, and a standard drain-check valve make the I-20 rotor top in its class.

#### Nozzle Racks

Large selection of nozzles to meet the needs of the most complex landscapes.



#### Easy Adjustable Arc

Simple through-the-top adjustment allows fine tuning of the coverage area.



# I-20 FEATURES & SPECIFICATIONS

## Features

- Plastic riser models: Shrub, 10 cm, 15 cm, 30 cm
- Stainless riser models: 10 cm, 15 cm
- Arc setting: 50° to 360°
- Factory-installed rubber cover
- Through-the-top arc adjustment
- Quick check arc mechanism
- Water lubricated gear drive
- Warranty period: 5 years
- Nozzle choices: 34
- Nozzle racks: 1.5 to 8.0 Blue, 2.0 LA to 4.5 Grey, 0.50 to 3.0 Black, 6.0 to 13.0 Green, MPR-20, MPR-30, MPR-35

## Operating Specifications

- Radius: 4.9 to 14 m
- Flow Rate: 0.07 to 3.23 m<sup>3</sup>/hr 1.2 to 53.8 l/min
- Recommended pressure range: 1.7 to 4.5 bar; 170 to 450 kPa
- Operating pressure range: 1.4 to 7 bar; 140 to 700 kPa
- Precipitation rates: 10 mm/hr approx.
- Nozzle trajectory: Std = 25°, Low angle = 13°

## Models



### I-20-00

Overall Height: 20 cm  
Exposed Diameter: 4.5 cm  
Inlet Size: 3/4"



### I-20-04

Overall Height: 19 cm  
Pop-up Height: 10 cm  
Exposed Diameter: 4.5 cm  
Inlet Size: 3/4"



### I-20-06

Overall Height: 25 cm  
Pop-up Height: 15 cm  
Exposed Diameter: 4.5 cm  
Inlet Size: 3/4"



### I-20-12

Overall Height: 43 cm  
Pop-up Height: 30 cm  
Exposed Diameter: 4.5 cm  
Inlet Size: 3/4"



*I-20 can be turned off at the head if needed*

**Website** [hunterindustries.com](http://hunterindustries.com) | **Customer Support** +1 760-752-6037 | **Technical Service** +1 760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Gene Smith, President, Landscape Irrigation and Outdoor Lighting

© 2022 Hunter Industries™. Hunter, the Hunter logo, and all other trademarks are property of Hunter Industries, registered in the U.S. and other countries. Please recycle.